

### SAFETY DATA SHEET

#### (Aerosol) Plus 10

According to the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practise, 2021.

SECTION 1: Identification: Pro	oduct identifier and chemical identity
Product identifier	
Product name	(Aerosol) Plus 10
Product No.	A202-7
Relevant identified uses of the	substance or mixture and uses advised against
Application	Car maintenance product. Cleaning agent. Engine cleaner.
Uses advised against	For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.
Details of the supplier of the s	afety data sheet
Supplier	Autosmart Australia 11 Darrambal Close Rathmines NSW 2283 Australia www.autosmartaustralia.com.au Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information) autosmart@autosmartaustralia.com.au
Contact Person	Mr. Russell Butler
Manufacturer	Autosmart International Ltd Lynn Lane Shenstone, nr Lichfield Staffordshire WS14 0DH Great Britain www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
Emergency telephone number	
Emergency telephone	NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003- NCEC" Local number +61 2 8 014 4558 General Information. Transport Information. Mild medical Information:- Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)
National emergency telephone number	Poison Information Hotline: 13 11 26

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Physical hazards	Aerosol 1 - H222, H229 Press. Gas, Compressed - H280
Health hazards	Eye Irrit. 2A - H319 STOT SE 3 - H336
Environmental hazards	Not Classified
Label elements	
Hazard pictograms	
Signal word	DANGER
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	<ul> <li>P210 Keep away from heat/ sparks/ open flames/ hot surfaces No smoking.</li> <li>P211 Do not spray on an open flame or other ignition source.</li> <li>P251 Pressurized container: Do not pierce or burn, even after use.</li> <li>P261 Avoid breathing vapour/ spray.</li> <li>P280 Wear protective gloves.</li> <li>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</li> </ul>
Supplemental label information	AUH066 Repeated exposure may cause skin dryness or cracking. For professional users only.
Contains	Naphtha (petroleum), hydrotreated heavy

#### Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

#### SECTION 3: Composition and information on ingredients

#### Mixtures

#### Naphtha (petroleum), hydrotreated heavy

CAS number: 64742-48-9

### Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

CAS number: 68476-85-7

Substance with a Community workplace exposure limit.

#### Classification

Flam. Gas 1 - H220 Press. Gas, Liquefied - H280 15<20%

60-100%

3<5%

1.5<1.75%

### (Aerosol) Plus 10

#### **XYLENE**

CAS number: 1330-20-7

Substance with a Community workplace exposure limit.

#### Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315

# dodecylbenzenesulphonic acid, compound with isopropylamine (1:1)

CAS number: 26264-05-1

#### Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

Description of first aid measure	
General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact	Rinse with water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.
Most important symptoms and effects, both acute and delayed	
General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

3/17

Inhalation	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Irritating to eyes.
Indication of any immediate m	edical attention and special treatment needed
Notes for the doctor	Treat symptomatically.
SECTION 5: Firefighting meas	sures
Extinguishing media	
Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Special hazards arising from t	he substance or mixture
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Vapours may form explosive mixtures with air.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.
SECTION 6: Accidental release measures	
Personal precautions, protective equipment and emergency procedures	
Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

Environmental precautions

**Environmental precautions** Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Approach the spillage from upwind. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

#### Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

#### SECTION 7: Handling and storage, including how the chemical may be safely used

#### Precautions for safe handling

Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.
Conditions for safe storage, inc	cluding any incompatibilities
Storage precautions	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50 °C/ 122 °F. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
Storage class	Chemical storage.
Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.
SECTION 8: Exposure controls and personal protection	

#### **Control parameters**

#### Occupational exposure limits

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): 1000 ppm 1800 mg/m<sup>3</sup>

#### XYLENE

Long-term exposure limit (8-hour TWA): NOHSC 80 ppm 350 mg/m<sup>3</sup> Short-term exposure limit (15-minute): NOHSC 150 ppm 655 mg/m<sup>3</sup> NOHSC = The National Occupational Health and Safety Commission.

Ingredient comments WEL = Workplace Exposure Limits

#### Naphtha (petroleum), hydrotreated heavy (CAS: 64742-48-9)

**Ingredient comments** No exposure limits known for ingredient(s).

#### dodecylbenzenesulphonic acid, compound with isopropylamine (1:1) (CAS: 26264-05-1)

Ingredient comments

No exposure limits known for ingredient(s).

#### Exposure controls

Protective equipment





Appropriate engineering controls	Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.
Environmental exposure	Keep container tightly sealed when not in use.

controls

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties	
Appearance	Liquid. Aerosol.
Colour	Blue.
Odour	Strong. Solvent.
Odour threshold	Not available.
рН	Not applicable.
Melting point	Not determined.
Initial boiling point and range	-40 ~ -2°C @ 1013 hPa
Flash point	-60°C Closed cup.
Evaporation rate	Not available.
Flammability Limit - Lower(%)	Lower flammable/explosive limit: 1.4 $\%$ Upper flammable/explosive limit: 10.9 $\%$
Vapour pressure	590 - 1760 kPa @ °C
Vapour density	~ 1.5 @ 15°C
Relative density	~ 0.510 @ 15°C
Solubility(ies)	Soluble in the following materials: Organic solvents. Insoluble in water.
Partition coefficient	log Pow: 2.3 - 2.8
Auto-ignition temperature	365°C
Decomposition Temperature	Not available.
Viscosity	Not determined.
Oxidising properties	Not applicable.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures. Information given is applicable to the major ingredient.
Volatile organic compound	This product contains a maximum VOC content of 695 g/l.
SECTION 10: Stability and reactivity	

Reactivity

See the other subsections of this section for further details.

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidising agents.
Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
SECTION 11: Toxicological in	formation
Information on toxicological ef	fects
Acute toxicity - oral	
Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	31,585.4
Acute toxicity - dermal	
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	28,406.99
Acute toxicity - inhalation	
Notes (inhalation LC <sub>50</sub> )	Based on available data the classification criteria are not met.
ATE inhalation (dusts/mists mg/l)	38.74
Skin corrosion/irritation Animal data	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation Serious eye damage/irritation	Causes serious eye irritation.
Respiratory sensitisation Respiratory sensitisation	Based on available data the classification criteria are not met.
Skin sensitisation Skin sensitisation	Based on available data the classification criteria are not met.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly carcinogenic to humans.
Reproductive toxicity Reproductive toxicity - fertility	Based on available data the classification criteria are not met.

Reproductive toxicity - development	Based on available data the classification criteria are not met.	
Specific target organ toxicity -	single exposure	
STOT - single exposure	STOT SE 3 - H336 May cause drowsiness or dizziness.	
Target organs	Central nervous system	
Specific target organ toxicity - repeated exposure		
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.	
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
Inhalation	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.	
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.	
Skin Contact	Repeated exposure may cause skin dryness or cracking.	
Eye contact	Irritating to eyes.	
Acute and chronic health hazards	Because of limited volume in an aerosol, and that the contents can hardly be swallowed, risk of poisoning is regarded to be small. Inhalation of vapour may cause: Sore throat. Pain in the chest. Coughing. Symptoms following overexposure may include the following: Diarrhoea. Severe abdominal pain.	
Route of exposure	Ingestion Inhalation Skin and/or eye contact	
Target Organs	Central nervous system	
Medical Symptoms	Prolonged or repeated exposure may cause the following adverse effects: Central nervous system depression. Difficulty in breathing. Unconsciousness.	
Medical considerations	Chronic respiratory and obstructive airway diseases. Skin disorders and allergies.	
Toxicological information on ingredients.		
Naphtha (petroleum), hydrotreated heavy		
Acute toxicity - oral		
Acute toxicity ora mg/kg)	al (LD₅o 5,000.0	
Species	Rat	
Acute toxicity - dermal		
Acute toxicity dermal (LD₅ 5,000.0		

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	5,000.0
Species	Rat
Acute toxicity - dermal	
Acute toxicity dermal (LD∞ mg/kg)	5,000.0
Species	Rabbit
	PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS
Skin corrosion/irritation	
Human skin model test	Scientifically unjustified.

Extreme pH	Scientifically unjustified.
Germ cell mutagenicity	
Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.
Reproductive toxicity	
Reproductive toxicity - fertility	Does not contain any substances known to be toxic to reproduction.
Specific target organ toxicit	y - single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Target organs	Central nervous system
Specific target organ toxicit	y - repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Target organs	Central nervous system
Aspiration hazard	
Aspiration hazard	Based on available data the classification criteria are not met.
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system. Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Intoxication. May cause discomfort. Vapour may irritate respiratory system/lungs.
Ingestion	May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. May cause discomfort if swallowed. No harmful effects expected from quantities likely to be ingested by accident.
Skin Contact	May cause defatting of the skin but is not an irritant.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Because of the product's quantity and composition, the health hazard is regarded as low.
Route of exposure	Inhalation Ingestion. Skin and/or eye contact
	XYLENE
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	4,300.0
Species	Rat
Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	2,000.0
Species	Rabbit

Notes (dermal LD₅₀)	Acute Tox. 4 - H312 Harmful in contact with skin.
ATE dermal (mg/kg)	1,100.0
Acute toxicity - inhalation	
Notes (inhalation LC <sub>50</sub> )	Acute Tox. 4 - H332 Harmful if inhaled.
ATE inhalation (dusts/mists mg/l)	1.5
Skin corrosion/irritation	
Animal data	Irritating.
Serious eye damage/irritat	ion
Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitisation	
Respiratory sensitisation	Based on available data the classification criteria are not met.
Skin sensitisation	
Skin sensitisation	Based on available data the classification criteria are not met.
Germ cell mutagenicity	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Not available.
Carcinogenicity	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
Reproductive toxicity	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxici	ty - single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxici	ty - repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Target organs	Respiratory system, lungs
Aspiration hazard	
Aspiration hazard	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness.

	Ingestion	May cause irritation.
	Skin Contact	Redness. Irritating to skin.
	Eye contact	No specific symptoms known.
	Route of exposure	Ingestion Inhalation Skin and/or eye contact
	Target Organs	No specific target organs known.
SECTION 1	2: Ecological information	
Ecotoxicity	-	arded as dangerous for the environment. However, large or frequent spills may have ous effects on the environment.
Ecological i	nformation on ingredients.	
		Naphtha (petroleum), hydrotreated heavy
	Ecotoxicity	The product is not expected to be toxic to aquatic organisms.
		PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS
	Ecotoxicity	The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
		XYLENE
	Ecotoxicity	The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
Toxicity	Based	on available data the classification criteria are not met.
Ecological i	nformation on ingredients.	
		PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS
	Acute aquatic toxicity	
	Acute toxicity - fish	Not determined.
	Acute toxicity - aquatic invertebrates	Not determined.
	Acute toxicity - aquatic plants	Not determined.
	Acute toxicity - microorganisms	Not determined.
	Acute toxicity - terrestrial	Not determined.
		XYLENE
	Acute aquatic toxicity	
	Acute toxicity - fish	LC50, 96 hours: 4.2 mg/l, Oncorhynchus mykiss (Rainbow trout)
	Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: > 2.93 mg/l, Daphnia magna
	Chronic aquatic toxicity	

Chronic toxicity - fish early NOEC, : 3.3 mg/l, Menidia peninsulae (Tidewater silverside) life stage

Chronic toxicity - aquatic NOEC, : 6.8 mg/l, Daphnia magna invertebrates

#### dodecylbenzenesulphonic acid, compound with isopropylamine (1:1)

Acute aquatic toxicity

Acute toxicity - fish	LC₅₀, 96 hours: 1-5 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: 15 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC₅₀, 72 hours: 10-300 mg/l, Algae

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

#### Ecological information on ingredients.

#### Naphtha (petroleum), hydrotreated heavy

Persistence and degradability	Volatile substances are degraded in the atmosphere within a few days.
	PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS
Persistence and degradability	Volatile substances are degraded in the atmosphere within a few days.
	XYLENE
Persistence and degradability	Volatile substances are degraded in the atmosphere within a few days.
dod	ecylbenzenesulphonic acid, compound with isopropylamine (1:1)
Persistence and degradability	The product is biodegradable.
Bioaccumulative potential	
Bioaccumulative Potential No data	available on bioaccumulation.
Partition coefficient log Pow	<i>r</i> : 2.3 - 2.8
Ecological information on ingredients.	
	Naphtha (petroleum), hydrotreated heavy
Bioaccumulative Potential	The product does not contain any substances expected to be bioaccumulating.
	PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS
Bioaccumulative Potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
Partition coefficient	log Pow: ~ 2.3 - 2.8

#### XYLENE

	Bioaccumulative Pe	otential	The product contains potentially bioaccumulating substances.
	Partition coefficient	:	log Pow: ~ 3.12
		dode	cylbenzenesulphonic acid, compound with isopropylamine (1:1)
	Bioaccumulative Po	otential	The product does not contain any substances expected to be bioaccumulating.
Mobility in s	oil		
Mobility		The proc surfaces	duct contains volatile organic compounds (VOCs) which will evaporate easily from all .
Ecological in	nformation on ingred	ients.	
			Naphtha (petroleum), hydrotreated heavy
	Mobility		The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
			PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS
	Mobility		The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
			XYLENE
	Mobility		The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
		dode	cylbenzenesulphonic acid, compound with isopropylamine (1:1)
	Mobility		The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.
Other adver	se effects		
Other adver	se effects	None kn	own.
Ecological in	nformation on ingred	ients.	
			PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS
	Other adverse effe	cts	None known.
SECTION 1	3: Disposal consider	ations	
Waste treat	ment methods		
General info		oroducts way. Dis comply v any loca nandling containe	eration of waste should be minimised or avoided wherever possible. Reuse or recycle wherever possible. This material and its container must be disposed of in a safe posal of this product, process solutions, residues and by-products should at all times with the requirements of environmental protection and waste disposal legislation and l authority requirements. When handling waste, the safety precautions applying to of the product should be considered. Care should be taken when handling emptied rs that have not been thoroughly cleaned or rinsed out. Empty containers or liners in some product residues and hence be potentially hazardous.

Disposal methods	Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

#### SECTION 14: Transport information

General	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.
UN number	
UN No. (ADG)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN proper shipping name	
Proper shipping name (ADG)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Transport hazard class(es)	
ADG class	2.1
ADG classification code	5F
ADG label	2.1
IMDG class	2.1
ICAO class/division	2.1

#### Transport labels



Packing group	
ADG packing group	None
IMDG packing group	None
ICAO packing group	None

#### Environmental hazards

Environmentally hazardous substance/marine pollutant No.

#### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-D, S-U

#### Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory info	SECTION 15: Regulatory information		
Safety, health and environme	ental regulations/legislation specific for the substance or mixture		
Guidance	Workplace Exposure Limits EH40.		
Schedule (SUSMP)	Schedule 5. Caution.		
Inventories			
Australia - AIIC			
The following ingredients are			
ALCOHOL, C9-11, ETHOXY	(LATED (9EO)		
Water			
1,4-bis(isopropylamino)anthi	1,4-bis(isopropylamino)anthraquinone		
dodecylbenzenesulphonic a	dodecylbenzenesulphonic acid, compound with isopropylamine (1:1)		
Alcohols, C9-11, Ethoxylated 2.5 EO			
Naphtha (petroleum), hydrotreated heavy			
XYLENE			
(R)-p-mentha-1,8-diene			
BENZYL ALCOHOL			
Linalool			
CITRAL			
CITRUS AURANTIUM DULO	CIS OIL		
CEDR-8-ENYL Methyl Keytone			
Terpineol			
Glycerine			
2,2'-iminodiethanol			
COCONUT DIETHANOLAM	IDE		
SECTION 16: Any other relev	vant information		

Abbreviations and acronyms ADG: Australian dangerous goods code used in the safety data sheet

- IATA: International air transport association.
- ICAO: Technical instructions for the safe transport of dangerous goods by air.
- IMDG: International maritime dangerous goods.
- CAS: Chemical abstracts service.
- ATE: Acute toxicity estimate.
- $LC_{50}:$  Lethal concentration to 50 % of a test population.
- LD<sub>50</sub>: Lethal dose to 50% of a test population (median lethal dose).
- $\mathsf{EC}_{50}\!\!: 50\%$  of maximal effective concentration.
- PBT: Persistent, bioaccumulative and toxic substance.
- vPvB: Very persistent and very bioaccumulative.

Classification abbreviations and acronyms	Aerosol = Aerosol Eye Irrit. = Eye irritation STOT SE = Specific target organ toxicity-single exposure
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain. www.autosmartinternational.com rbutler@autosmart.co.uk Tel +44 (0)1543 481616
Revision date	23/06/2021
Revision	6
Supersedes date	12/05/2021
SDS No.	10313
SDS status	Approved.
Hazard statements in full	<ul> <li>H220 Extremely flammable gas.</li> <li>H226 Flammable liquid and vapour.</li> <li>H229 Pressurised container: may burst if heated.</li> <li>H280 Contains gas under pressure; may explode if heated.</li> <li>H302 Harmful if swallowed.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H312 Harmful in contact with skin.</li> <li>H315 Causes skin irritation.</li> <li>H318 Causes serious eye damage.</li> <li>H319 Causes serious eye irritation.</li> <li>H332 Harmful if inhaled.</li> <li>H336 May cause drowsiness or dizziness.</li> </ul>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.