

SAFETY DATA SHEET

(Aerosol) Silicone Spray Starburst

According to the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practise, 2021.

SECTION 1: Identification: Product identifier and chemical identity

Product identifier

Product name (Aerosol) Silicone Spray Starburst

Product No. A77-9

Relevant identified uses of the substance or mixture and uses advised against

Application Car maintenance product. - Dressing

Uses advised against For professional use only. This product is not recommended for any industrial, professional or

consumer use other than the Identified uses above.

Details of the supplier of the safety data sheet

Supplier Autosmart Australia

11 Darrambal Close

Rathmines NSW 2283 Australia

www.autosmartaustralia.com.au

Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport

Information. Mild Medical Information) autosmart@autosmartaustralia.com.au

Contact Person Mr. Russell Butler

Manufacturer Autosmart International Ltd..

Lynn Lane

Shenstone, nr Lichfield Staffordshire WS14 0DH

Great Britain

www.autosmartinternational.com

Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

info@autosmartinternational.com

Emergency telephone number

Emergency telephone NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call

NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003-

NCEC"

Local number +61 2 8 014 4558

General Information. Transport Information. Mild medical Information:-

Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

National emergency telephone Poison Information Hotline: 13 11 26

number

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Physical hazards Aerosol 1 - H222, H229 Press. Gas, Compressed - H280

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Hazard pictograms









Signal word

DANGER

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Supplemental label

information

For professional users only.

AUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

SECTION 3: Composition and information on ingredients

Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

30<60%

CAS number: 68476-85-7

Substance with a Community workplace exposure limit.

Classification

Flam. Gas 1 - H220

Press. Gas, Liquefied - H280

(Aerosol) Silicone Spray Starburst

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-

30<60%

hexane

CAS number: 64742-49-0

Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

(R)-p-mentha-1,8-diene 0.1<0.2%

CAS number: 5989-27-5

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Skin Sens. 1B - H317 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin Contact Rinse with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. Wash

contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

Most important symptoms and effects, both acute and delayed

(Aerosol) Silicone Spray Starburst

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic

effect.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Redness. Irritating to skin.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder Suitable extinguishing media

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. If

aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised

contents and propellant.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

authorities.

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate.

Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Approach the spillage from upwind. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store in accordance with local regulations. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50 °C/ 122 °F. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class Miscellaneous hazardous material storage.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

SECTION 8: Exposure controls and personal protection

Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): 1000 ppm 1800 mg/m³

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (CAS: 64742-49-0)

Ingredient comments No exposure limits known for ingredient(s).

(R)-p-mentha-1,8-diene (CAS: 5989-27-5)

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: >0.2mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance Aerosol. Liquid.

Colour Clear liquid.

Odour Pleasant, agreeable.

Odour threshold Not available.

pH Not applicable.

Melting point Not determined.

Initial boiling point and range -40 ~ -2°C @ 1013 hPa

(Aerosol) Silicone Spray Starburst

Flash point -60°C Closed cup.

Evaporation rate Not available.

Flammability Limit - Lower(%) Lower flammable/explosive limit: 1.4 % Upper flammable/explosive limit: 10.9 %

Vapour pressure 590 - 1760 kPa @ °C

Vapour density ~ 1.5 @ 15°C

Relative density ~ 0.510 @ 15°C

Solubility(ies) Soluble in the following materials: Organic solvents. Insoluble in water.

Partition coefficient log Pow: 2.3 - 2.8

Auto-ignition temperature 365°C

Decomposition Temperature Not available.

Viscosity Not determined.

Oxidising properties Not applicable.

Comments Information declared as "Not available" or "Not applicable" is not considered to be relevant to

the implementation of the proper control measures. Information given is applicable to the

major ingredient.

Volatile organic compound This product contains a maximum VOC content of 587 g/litre.

SECTION 10: Stability and reactivity

Reactivity There are no known reactivity hazards associated with this product.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidising agents.

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised

container: may burst if heated

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

Notes (oral LD₅o) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

(Aerosol) Silicone Spray Starburst

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Human skin model test Scientifically unjustified.

Extreme pH Scientifically unjustified.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance/a group of substances which may cause cancer. IARC Group 3 Not

classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, disziness, disorientation, vertigo. Narcotic

effect.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin Contact Redness. Irritating to skin.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Acute and chronic health

hazards

Because of the product's quantity and composition, the health hazard is regarded as low.

Route of exposure Ingestion Inhalation Skin and/or eye contact

(Aerosol) Silicone Spray Starburst

Target Organs Central nervous system

Medical Symptoms No specific symptoms noted, but this chemical may still have adverse health impact, either in

general or on certain individuals.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Skin corrosion/irritation

Human skin model test Scientifically unjustified.

Extreme pH Scientifically unjustified.

Germ cell mutagenicity

Genotoxicity - in vivoThis substance has no evidence of mutagenic properties.

Reproductive toxicity

Reproductive toxicity -

fertility

Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Target organs Central nervous system

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information Prolonged and repeated contact with solvents over a long period may lead to

permanent health problems.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect

central nervous system. Symptoms following overexposure may include the

following: Headache. Nausea, vomiting. Intoxication. May cause discomfort. Vapour

may irritate respiratory system/lungs.

Ingestion May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset

stomach. May cause discomfort if swallowed. No harmful effects expected from

quantities likely to be ingested by accident.

Skin Contact May cause defatting of the skin but is not an irritant.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

Because of the product's quantity and composition, the health hazard is regarded

hazards as low.

Route of exposure Inhalation Ingestion. Skin and/or eye contact

(R)-p-mentha-1,8-diene

Carcinogenicity

(Aerosol) Silicone Spray Starburst

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Skin Contact

The product contains a small amount of sensitising substance. May cause

sensitisation or allergic reactions in sensitive individuals.

SECTION 12: Ecological information

Ecotoxicity The product contains a substance which is harmful to aquatic organisms.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Ecotoxicity The product components are not classified as environmentally hazardous.

However, large or frequent spills may have hazardous effects on the environment.

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic

Not determined.

invertebrates

Acute toxicity - aquatic plants Not determined.

Acute toxicity -Not determined.

microorganisms

Acute toxicity - terrestrial Not determined.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic

invertebrates

Not determined.

Acute toxicity - aquatic

plants

Not determined.

Acute toxicity microorganisms Not determined.

Acute toxicity - terrestrial

Not determined.

(R)-p-mentha-1,8-diene

Acute aquatic toxicity

 $0.1 < L(E)C50 \le 1$ LE(C)50

M factor (Acute) 1

Chronic aquatic toxicity

NOEC 0.01 < NOEC ≤ 0.1

Degradability Non-rapidly degradable

(Aerosol) Silicone Spray Starburst

M factor (Chronic) 1

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Persistence and degradability

Volatile substances are degraded in the atmosphere within a few days.

(R)-p-mentha-1,8-diene

Persistence and degradability

Volatile substances are degraded in the atmosphere within a few days.

Bioaccumulative potential

Bioaccumulative Potential No data available on bioaccumulation.

Partition coefficient log Pow: 2.3 - 2.8

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Bioaccumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

Partition coefficient log Pow: ~ 2.3 - 2.8

(R)-p-mentha-1,8-diene

Bioaccumulative Potential The product contains potentially bioaccumulating substances.

Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces.

(R)-p-mentha-1,8-diene

Mobility The product is insoluble in water.

Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Other adverse effects None known.

SECTION 13: Disposal considerations

Waste treatment methods

General information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

UN number

UN No. (ADG) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN proper shipping name

Proper shipping name (ADG) AEROSOLS

Proper shipping name

(IMDG)

AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Transport hazard class(es)

ADG class 2.1

ADG label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



Packing group

Not applicable.

Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-D, S-U

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Schedule (SUSMP) Schedule 5. Caution.

Inventories

Australia - AIIC

All the ingredients are listed or exempt.

SECTION 16: Any other relevant information

General information This product has been manufactured under ISO 9001 and ISO 14001 Quality and

Environmental Management Systems.

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire,

WS14 0DH, Great Britain.

www.autosmartinternational.com

rbutler@autosmart.co.uk Tel +44 (0)1543 481616

Revision date 12/05/2021

Revision 9

Supersedes date 17/10/2019

SDS No. 10335

SDS status Approved.

Hazard statements in full H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.