

SAFETY DATA SHEET

Methylated Spirits

According to the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practise, 2021.

SECTION 1: Identification: Pro	SECTION 1: Identification: Product identifier and chemical identity	
Product identifier		
Product name	Methylated Spirits	
Relevant identified uses of the	substance or mixture and uses advised against	
Application	Raw Material	
Uses advised against	For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.	
Details of the supplier of the safety data sheet		
Supplier	Autosmart Australia 11 Darrambal Close Rathmines NSW 2283 Australia www.autosmartaustralia.com.au Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport Information. Mild Medical Information) autosmart@autosmartaustralia.com.au	
Contact Person	Mr. Russell Butler	
Emergency telephone number		
Emergency telephone	NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003- NCEC" Local number +61 2 8 014 4558 General Information. Transport Information. Mild medical Information:- Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)	
National emergency telephone number	Poison Information Hotline: 13 11 26	

SECTION 2: Hazard(s) identification

Classification of the substance or mixture	
Physical hazards	Flam. Liq. 2 - H225
Health hazards	Eye Irrit. 2A - H319
Environmental hazards	Not Classified
Label elements	

Hazard pictograms



Signal word	DANGER
Hazard statements	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.
Precautionary statements	 P210 Keep away from heat/ sparks/ open flames/ hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/ bond container and receiving equipment. P243 Take precautionary measures against static discharge. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool.
Supplemental label information	For professional users only.

Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

SECTION 3: Composition and information on ingredients

Mixtures	
ETHANOL	60-100%
CAS number: 64-17-5	
Substance with a Community workplace exposure limit.	
Classification	

Flam. Liq. 2 - H225

Diethyl Phthalate

CAS number: 84-66-2

Substance with a Community workplace exposure limit.

Classification

Not Classified

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

Description of first aid measures

General information

Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

0.5<0.7%

Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.	
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.	
Skin Contact	Rinse with water.	
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.	
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.	
Most important symptoms and	effects, both acute and delayed	
General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.	
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.	
Skin contact	Prolonged contact may cause dryness of the skin.	
Eye contact	May cause temporary eye irritation.	
Indication of any immediate m	edical attention and special treatment needed	
Notes for the doctor	Treat symptomatically.	
SECTION 5: Firefighting meas	sures	
Extinguishing media		
Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Special hazards arising from the substance or mixture		
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.	
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.	
Advice for firefighters		

Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.	
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.	
Hazchem Code	•2YE	
SECTION 6: Accidental release measures		
Personal precautions, protective equipment and emergency procedures		
Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as	

unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

Environmental precautions

Environmental precautions Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills
	immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No
	smoking, sparks, flames or other sources of ignition near spillage. Use only non-sparking
	tools. Use explosion-proof electrical equipment. Do not allow material to enter confined
	spaces, due to the risk of explosion. Approach the spillage from upwind. Small Spillages: If
	the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it
	is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable
	waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area.
	Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and
	absorb spillage with sand, earth or other non-combustible material. Place waste in labelled,
	sealed containers. Clean contaminated objects and areas thoroughly, observing
	environmental regulations. The contaminated absorbent may pose the same hazard as the
	spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing
	with a spillage. Dispose of waste to licensed waste disposal site in accordance with the
	requirements of the local Waste Disposal Authority.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Usage precautions	Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In use may form flammable/explosive vapour-air mixture. Vapours may accumulate on the floor and in low-lying areas. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.
Conditions for safe storage, in	cluding any incompatibilities
Storage precautions	Store in accordance with local regulations. Eliminate all sources of ignition. Take precautionary measures against static discharges. Earth container and transfer equipment to eliminate sparks from static electricity. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak- tight, jointless and not absorbent.
Storage class	Flammable liquid storage.
Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.
SECTION 8: Exposure control	s and personal protection
Control parameters	

Occupational exposure limits

ETHANOL

Long-term exposure limit (8-hour TWA): 1000 ppm 1880 mg/m³

Diethyl Phthalate

Long-term exposure limit (8-hour TWA): 5 mg/m³

Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilating equipment.

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties	
Appearance	Clear liquid.
Colour	Colourless.
Odour	Characteristic.
рН	Not applicable.
Melting point	-117°C
Initial boiling point and range	78°C @ 1013 mbar
Flash point	13°C Closed cup.
Evaporation rate	2.53 (butyl acetate = 1)
Flammability Limit - Lower(%)	Upper flammable/explosive limit: 19 $\%$ Lower flammable/explosive limit: 3.5 $\%$
Vapour pressure	5.9 kPa @ 20°C
Vapour density	~ 1.59

Relative density	~ 0.790 - 0.810 @ 20°C
Auto-ignition temperature	392°C
Volatile organic compound	This product contains a maximum VOC content of 100 %.
SECTION 10: Stability and rea	activity
Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidising agents.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition.
Materials to avoid	Oxidising materials. Acids - oxidising.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
SECTION 11: Toxicological in	formation
Information on toxicological ef	fects
Acute toxicity - oral Notes (oral LD₅)	Based on available data the classification criteria are not met.
Acute toxicity - dermal Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - inhalation Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
Skin corrosion/irritation Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitisation Respiratory sensitisation	Based on available data the classification criteria are not met.
Skin sensitisation Skin sensitisation	Based on available data the classification criteria are not met.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.
Reproductive toxicity Reproductive toxicity - fertility	Based on available data the classification criteria are not met.

Reproductive toxicity -	Based on available data the classification criteria are not met.		
development			
Specific target organ toxicity -			
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.		
Specific target organ toxicity -			
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.		
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.		
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.		
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.		
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.		
Skin Contact	Prolonged contact may cause dryness of the skin.		
Eye contact	May cause temporary eye irritation.		
Route of exposure	Ingestion Inhalation Skin and/or eye contact		
Target Organs	No specific target organs known.		
SECTION 12: Ecological information			
Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.		
Toxicity	Based on available data the classification criteria are not met.		
Persistence and degradability			
Persistence and degradability	The product is readily biodegradable.		
Bioaccumulative potential			
Bioaccumulative Potential	No data available on bioaccumulation.		
Mobility in soil			
Mobility	The product is water-soluble and may spread in water systems. The product is non-volatile.		
Other adverse effects			
Other adverse effects	None known.		
SECTION 13: Disposal consid	SECTION 13: Disposal considerations		
Waste treatment methods			
General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.		

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible. Vapour from residual product may create a highly flammable or explosive atmosphere inside the container. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not cut or weld used containers unless they have been thoroughly cleaned internally.

SECTION 14: Transport information

UN number	
UN No. (ADG)	1170
UN No. (IMDG)	1170
UN No. (ICAO)	1170
UN proper shipping name	
Proper shipping name (ADG)	ETHANOL
Proper shipping name (IMDG)	ETHANOL
Proper shipping name (ICAO)	ETHANOL
Transport hazard class(es)	
ADG class	3
ADG classification code	F1
ADG label	3
IMDG class	3
ICAO class/division	3
Transport labels	

Packing group

ADG packing group	II
IMDG packing group	II
ICAO packing group	II

Environmental hazards

Environmentally hazardous substance/marine pollutant No.

Special precautions for user	
------------------------------	--

EmS	F-E, S-D
Hazchem Code	•2YE

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Schedule (SUSMP)

No Poison Schedule number allocated

Inventories

Australia - AIIC

All the ingredients are listed or exempt.

SECTION 16: Any other relevant information

Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain. www.autosmartinternational.com rbutler@autosmart.co.uk Tel +44 (0)1543 481616
Revision date	1/09/2021
Revision	2
Supersedes date	18/10/2016
SDS No.	21268
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.