

Revision: 2

SAFETY DATA SHEET

Evo 5

According to the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practise, 2021.

SECTION 1: Identification: Product identifier and chemical identity		
Product identifier		
Product name	Evo 5	
Relevant identified uses of the	substance or mixture and uses advised against	
Application	Car maintenance product Polish.	
Uses advised against	For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.	
Details of the supplier of the sa	afety data sheet	
Supplier	Autosmart Australia 11 Darrambal Close Rathmines	
	NSW 2283 Australia	
	www.autosmartaustralia.com.au	
	Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST) (General Information. Transport	
	Information. Mild Medical Information)	
	autosmart@autosmartaustralia.com.au	
Contact Person	Mr. Russell Butler	
Emergency telephone number		
Emergency telephone	NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003-NCEC"	
	Local number +61 2 8 014 4558	
	General Information. Transport Information. Mild medical Information:-	
	Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)	
National emergency telephone number	Poison Information Hotline: 13 11 26	
SECTION 2: Hazard(s) identifi	cation	

Classification of the substance or mixturePhysical hazardsNot ClassifiedHealth hazardsNot ClassifiedEnvironmental hazardsNot ClassifiedLabel elementsHazard statementsHazard statementsNC Not Classified

Precautionary statements	P280 Wear protective gloves. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Supplemental label information	For professional users only.

Other hazards

SECTION 4: First aid measures

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

Mixtures	
Distillates (petroleum), hydro- treated light	20<30%
CAS number: 64742-47-8	
Classification	
Flam. Liq. 4 - H227	
Asp. Tox. 1 - H304	
Aluminium oxide	10<15%
CAS number: 1344-28-1	
Substance with a Community workplace exposure limit.	
Classification	
Not Classified	
Aluminium oxide	5<109
CAS number: 1344-28-1	
Substance with a Community workplace exposure limit.	
Classification	
Not Classified	
White Mineral Oil (Petroleum)	5<10%
CAS number: 8042-47-5	
Classification	
Asp. Tox. 1 - H304	
Aluminium Silicate	3<5%
CAS number: 1332-58-7	
Substance with a Community workplace exposure limit.	
Classification	
Not Classified	

Description of first aid measures

Description of first aid measur			
General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.		
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.		
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.		
Skin Contact	Rinse with water.		
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.		
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.		
Most important symptoms and	Most important symptoms and effects, both acute and delayed		
General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.		
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.		
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.		
Skin contact	Prolonged contact may cause dryness of the skin.		
Eye contact	May cause temporary eye irritation.		
Indication of any immediate m	edical attention and special treatment needed		
Notes for the doctor	Treat symptomatically.		
SECTION 5: Firefighting meas	sures		
Extinguishing media			
Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.		
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.		
Special hazards arising from t	he substance or mixture		
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.		
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.		
Advice for firefighters			

Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.
SECTION 6: Accidental release measures	
Personal precautions, protective equipment and emergency procedures	

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

Environmental precautions

Environmental precautions Slightly soluble in water. Aquatic toxicity is unlikely to occur. However, large or frequent spills may have hazardous effects on the environment. Absorb spillage with non-combustible, absorbent material. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.	
Conditions for safe storage, inc	luding any incompatibilities	
Storage precautions	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.	
Storage class	Unspecified storage.	
Specific end use(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.	
SECTION 8: Exposure controls	and personal protection	
Control parameters		
Occupational exposure limits		
Aluminium oxide		
Long-term exposure limit (8-hour TWA): 10 mg/m ³		
Long-term exposure limit (8-hour TWA): 10 mg/m ³		
Aluminium oxide		
Long-term exposure limit (8-hour TWA): 10 mg/m³		
Aluminium Silicate		
Long-term exposure limit (8-hour TWA): 10 mg/m³		

White Mineral Oil (Petroleum) (CAS: 8042-47-5)

Ingredient comments

No exposure limits known for ingredient(s).

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: >0.2mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Viscous liquid. Emulsion.
Colour	Orange.
Odour	Pleasant, agreeable.
Odour threshold	Not available.
рН	Not applicable.
Initial boiling point and range	> 100°C @ 760 mm Hg
Flash point	62°C Closed cup.
Evaporation rate	Not available.

Flammability Limit - Lower(%)	Not available.	
Other flammability	This product does not sustain combustion, according to the sustained combustibility test L.2, Part III, section 32 of the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.	
Vapour pressure	>0.04 kPa @ 20°C	
Vapour density	Not available.	
Relative density	1.070 @ (20°C)°C	
Solubility(ies)	Slightly soluble in water.	
Partition coefficient	Not available.	
Auto-ignition temperature	Not available.	
Decomposition Temperature	Not available.	
Viscosity	Kinematic viscosity > 20.5 mm²/s.	
Oxidising properties	Not applicable.	
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.	
Volatile organic compound	This product contains a maximum VOC content of 310 g/litre.	
SECTION 10: Stability and rea	activity	
Reactivity	See the other subsections of this section for further details.	
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.	
Possibility of hazardous reactions	No potentially hazardous reactions known.	
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Containers can burst violently or explode when heated, due to excessive pressure build-up.	
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.	
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.	
SECTION 11: Toxicological information		
Information on toxicological eff	fects	
Acute toxicity - oral Notes (oral LD₅o)	Based on available data the classification criteria are not met.	
Acute toxicity - dermal		
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.	
Acute toxicity - inhalation Notes (inhalation LC∞)	Based on available data the classification criteria are not met.	

Skin corrosion/irritation

Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation Serious eye damage/irritation	Based on available data the classification criteria are not met.
Respiratory sensitisation Respiratory sensitisation	Based on available data the classification criteria are not met.
Skin sensitisation Skin sensitisation	Based on available data the classification criteria are not met.
Germ cell mutagenicity	
Genotoxicity - in vitro Carcinogenicity	Based on available data the classification criteria are not met.
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
Reproductive toxicity Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity -	single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxicity -	repeated exposure
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
	Based on available data the classification criteria are not met. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Aspiration hazard	The severity of the symptoms described will vary dependent on the concentration and the
Aspiration hazard General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Aspiration hazard General information Inhalation	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged inhalation of high concentrations may damage respiratory system. Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may
Aspiration hazard General information Inhalation Ingestion	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged inhalation of high concentrations may damage respiratory system. Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Aspiration hazard General information Inhalation Ingestion Skin Contact	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged inhalation of high concentrations may damage respiratory system. Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Prolonged contact may cause dryness of the skin.
Aspiration hazard General information Inhalation Ingestion Skin Contact Eye contact	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged inhalation of high concentrations may damage respiratory system. Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Prolonged contact may cause dryness of the skin. May cause temporary eye irritation.

Distillates (petroleum), hydro- treated light

Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	5,000.0
Species	Rat
Acute toxicity - dermal	

Acute toxicity dermal (LD₅₀ mg/kg)	2,000.0	
Species	Rabbit	
Skin corrosion/irritation		
Animal data	Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). Not irritating.	
Human skin model test	Not available.	
Serious eye damage/irritation		
Serious eye damage/irritation	Not irritating.	
Respiratory sensitisation		
Respiratory sensitisation	There is no evidence that the material can lead to respiratory hypersensitivity.	
Skin sensitisation		
Skin sensitisation	Buehler test: - Guinea pig: Not sensitising.	
Germ cell mutagenicity		
Genotoxicity - in vitro	: Negative. This substance has no evidence of mutagenic properties.	
Genotoxicity - in vivo	: Negative. This substance has no evidence of mutagenic properties.	
Carcinogenicity		
Carcinogenicity	There is no evidence that the product can cause cancer.	
Specific target organ toxicit		
STOT - repeated exposure	NOAEL 750 mg/kg, Oral, Rat	
Inhalation	No specific health hazards known.	
Ingestion	Harmful: may cause lung damage if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.	
Skin Contact	No specific health hazards known.	
Eye contact	No specific health hazards known.	
Medical Symptoms	Skin irritation.	
	Aluminium oxide	
Toxicological effects	No data recorded.	
Other health effects	There is no evidence that the product can cause cancer.	
	Aluminium oxide	
Toxicological effects	No data recorded.	
Other health effects	There is no evidence that the product can cause cancer.	

White Mineral Oil (Petroleum)

	ou	-			
	Other health effects	There is no evidence that the product can cause cancer.			
	Acute toxicity - oral				
	Acute toxicity oral (LD₅₀ mg/kg)	2,000.0			
	Species	Rat			
	Acute toxicity - dermal				
	Acute toxicity dermal (LD₅₀ mg/kg)	2,000.0			
	Species	Rabbit			
	Respiratory sensitisation				
	Respiratory sensitisation	Not sensitising.			
	Skin sensitisation				
	Skin sensitisation	Not sensitising.			
		Aluminium Silicate			
	Toxicological effects	No data recorded.			
	Other health effects	There is no evidence that the product can cause cancer.			
SECTION 12: Ecological information					
Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.					
Ecological ir	formation on ingredients.				
		Distillates (petroleum), hydro- treated light			
	Ecotoxicity	The product components are not classified as environmentally hazardous.			
		However, large or frequent spills may have hazardous effects on the environment.			
		White Mineral Oil (Petroleum)			
	Ecotoxicity	The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.			
Toxicity	Based or	n available data the classification criteria are not met.			
Ecological information on ingredients.					
		Distillates (petroleum), hydro- treated light			
	Acute aquatic toxicity				
	Acute toxicity - fish	LC₅₀, 96 hours: > 2-5 mg/l, Fish			
	Acute toxicity - aquatic invertebrates	EC₅₀, 48 hours: 1.4 mg/l, Daphnia magna			
	Acute toxicity - aquatic plants	IC₅₀, 72 hours: 1-3 mg/l, Algae			
White Mineral Oil (Petroleum)					

	Acute aquatic toxicity				
	Acute toxicity - fish	LC50, 96 hours: > 400 000 , Oncorhynchus mykiss (Rainbow trout)			
	Acute toxicity - aquatic invertebrates	, 96 hours: > 500 000 , Marinewater invertebrates			
Persistence	and degradability				
Persistence	and degradability The deg	gradability of the product is not known.			
Ecological in	nformation on ingredients.				
		Aluminium oxide			
	Persistence and degradability	The product is not biodegradable.			
		Aluminium oxide			
	Persistence and degradability	The product is not biodegradable.			
	White Mineral Oil (Petroleum)				
	Persistence and degradability	The product is expected to be slowly biodegradable.			
		Aluminium Silicate			
	Persistence and degradability	The product is not biodegradable.			
Bioaccumul	ative potential				
Bioaccumul	ative Potential No data	a available on bioaccumulation.			
Partition coe	efficient Not ava	ilable.			
Ecological information on ingredients.					
		Distillates (petroleum), hydro- treated light			
	Bioaccumulative Potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.			
Aluminium oxide					
	Bioaccumulative Potential	Accumulates in soil and sediment.			
		Aluminium oxide			
	Bioaccumulative Potential	Accumulates in soil and sediment.			
White Mineral Oil (Petroleum)					
	Bioaccumulative Potential	The product does not contain any substances expected to be bioaccumulating.			

Aluminium Silicate

Bioaccumulative Potential Accumulates in soil and sediment.

Mobility in soil

Mobility

The product is partly soluble in water and may spread in the aquatic environment. The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients.

Distillates (petroleum), hydro- treated light		
Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water and will spread on the water surface.	
Henry's law cons	tant Not available.	
	Aluminium oxide	
Mobility	Not considered mobile.	
	Aluminium oxide	
Mobility	Not considered mobile.	
	White Mineral Oil (Petroleum)	
Mobility	The product is insoluble in water and will spread on the water surface.	
	Aluminium Silicate	
Mobility	Not considered mobile.	
Other adverse effects		
Other adverse effects	None known.	
SECTION 13: Disposal consid	erations	
Waste treatment methods		
General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.	
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.	
SECTION 14: Transport inform	nation	

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADG).

UN number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

No transport warning sign required.

Packing group

Not applicable.

Environmental hazards

Environmentally hazardous substance/marine pollutant No.

Special precautions for user

Not applicable.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
	National Code of Practice for the Preparation of Material Safety Data Sheets.
	Approved Criteria for Classifying Hazardous Substances.
	Exposure Standards for Atmospheric Contaminants in the Occupational Environment.
	Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in
	the Occupational Environment.
	National Code of Practice for the Labelling of Workplace Substances.
	National Model Regulations for the Control of Workplace Hazardous Substances.
	National Code of Practice for the Control of Workplace Hazardous Substances.
	National Standard for the Storage and Handling of Workplace Dangerous Goods.
	National Code of Practice for the Storage and Handling of Workplace Dangerous Goods.
	Guidance Note for Placarding Stores for Dangerous Goods and Specified Hazardous
	Substances. Guidance Note for the Assessment of Health Risks Arising from Hazardous Substances in the Workplace.
	National Standard for the Control of Major Hazard Facilities. National Code of Practice for the
	Control of Major Hazard Facilities.
Schedule (SUSMP)	No Poison Schedule number allocated
Inventories	
Australia - AIIC	

All the ingredients are listed or exempt.

SECTION 16: Any other relevant information

Abbreviations and acronyms used in the safety data sheet	ADG: Australian dangerous goods code
	 IATA: International air transport association. ICAO: Technical instructions for the safe transport of dangerous goods by air. IMDG: International maritime dangerous goods. CAS: Chemical abstracts service. ATE: Acute toxicity estimate. LC₅₀: Lethal concentration to 50 % of a test population. LD₅₀: Lethal dose to 50% of a test population (median lethal dose). EC₅₀: 50% of maximal effective concentration. PBT: Persistent, bioaccumulative and toxic substance. vPvB: Very persistent and very bioaccumulative.
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Prepared by Autosmart International Ltd, Lynn Lane, Shenstone, Lichfield, Staffordshire, WS14 0DH, Great Britain. www.autosmartinternational.com rbutler@autosmart.co.uk Tel +44 (0)1543 481616
Revision date	7/06/2021
Revision	2
Supersedes date	7/05/2019
SDS No.	21712
SDS status	Approved
	Approved.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.