

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations Issue date: 26/04/2024 Version: 1.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Trade name : (Aerosol) 20/20
Product code : 003498000027

1.2. Other means of identification

Synonyms : ATTW001D

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Glass cleaner

Restrictions on use : For professional use only

1.4. Details of manufacturer or importer

Autosmart Australia
11 Darrambal Close

Rathmines NSW 2283 NSW

Australia

T 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

autosmart@autosmartaustralia.com.au - www.autosmartaustralia.com.au

1.5. Emergency phone number

Emergency number : NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident),

Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART

29003-NCEC"

Local number +61 2 8 014 4558

General Information. Transport Information. Mild medical Information:-

Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1 H222;H229
Gases under pressure : Compressed gas H280
Serious eye damage/eye irritation, Category 2A H319

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)







mark

Flame Gas cylin

Gas cylinder Exclamation

Signal word (GHS AU) : Danger

Contains : Propan-2-ol (8.6274 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H280 - Contains gas under pressure; may explode if heated

H319 - Causes serious eye irritation

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing vapours, spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, eye protection.

P264 - Wash contaminated skin thoroughly after handling.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice, medical attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	68476-85-7	40	Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Flam. Liq. 1, H224
Propan-2-ol	67-63-0	8.6274	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-butoxyethanol	111-76-2	3.375	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation), H331 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Other substances (not contributing to the classification of this product)	-	48	-

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this

material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

26/04/2024 (Issue date) AU - en 2/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and

eyes. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

26/04/2024 (Issue date) AU - en 3/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Storage conditions : Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures

exceeding 50 °C/ 122 °F.

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Propan-2-ol (67-63-0)			
Australia - Occupational Exposure Limits			
Local name	Isopropyl alcohol (Propan-2-ol)		
OES TWA	983 mg/m³		
	400 ppm		
OES STEL	1230 mg/m³		
	500 ppm		
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)		
2-butoxyethanol (111-76-2)			
Australia - Occupational Exposure Limits			
Local name	2-Butoxyethanol (Butyl cellosolve; Butyl glycol; Ethylene glycol monobutyl ether; Glycol monobutyl ether)		
OES TWA	96.9 mg/m³		
	20 ppm		
OES STEL	242 mg/m³		
	50 ppm		
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.		
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)		
Petroleum gases, liquefied (Contains < 0.1%	1,3-butadiene) (68476-85-7)		
Australia - Occupational Exposure Limits			
Local name	LPG (liquified petroleum gas)		
OES TWA	1800 mg/m³		
	1000 ppm		
Remark (AU)	Carcinogenicity Category 1B - Presumed to have a carcinogenic potential for humans. The classification of a substance into this category is based largely on animal evidence where there is sufficient evidence to demonstrate carcinogenicity in animals or where there is limited evidence of carcinogenicity in humans and animals.		
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)		

8.2. Monitoring methods

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Wear recommended personal protective equipment.

Materials for protective clothing : The following Australian and New Zealand Standards will provide general advice regarding

safety clothing and equipment: Industrial Clothing: AS2919.

26/04/2024 (Issue date) AU - en 4/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Hand protection : Protective gloves. The following Australian and New Zealand Standards will provide general

advice regarding safety clothing and equipment: Protective Gloves: AS 2161.

Eye protection : Safety glasses. The following Australian and New Zealand Standards will provide general

advice regarding safety clothing and equipment: Industrial Eye Protection: AS1336 and

AS/NZS 1337.

Skin and body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. The following

Australian and New Zealand Standards will provide general advice regarding safety clothing

and equipment: Respiratory equipment: AS/NZS 1715.

Personal protective equipment symbol(s)







Environmental exposure controls

: Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance : No data available
Colour : Colourless.
Odour : Odourless.
Odour threshold : No data available
pH : No data available
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : Melting point: Not applicable

Boiling point : No data available

Flash point : < -40 °C

Auto-ignition temperature : No data available Flammability : No data available Vapour pressure : No data available Relative density : No data available Density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : No data available Minimum ignition energy : No data available

VOC content : 394 g/l

Fat solubility : No data available

SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.

Chemical stability : No additional information available Possibility of hazardous reactions : No additional information available

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of

ignition.

Incompatible materials : No additional information available Hazardous decomposition products : No additional information available

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

26/04/2024 (Issue date) AU - en 5/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Propan-2-ol (67-63-0)				
LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)			
Skin corrosion/irritation :	Not classified			
Serious eye damage/irritation :	Causes serious eve irritation.			
Respiratory or skin sensitisation :	Not classified			
Germ cell mutagenicity :	Not classified			
Carcinogenicity :	Not classified			
Reproductive toxicity :	Not classified			
STOT-single exposure :	Not classified			
Propan-2-ol (67-63-0)				
STOT-single exposure	May cause drowsiness or dizziness.			
2-butoxyethanol (111-76-2)				
STOT-single exposure	May cause respiratory irritation.			
STOT-repeated exposure :	Not classified			
2-butoxyethanol (111-76-2)				
NOAEL (subacute, oral, animal/female, 28 days)	≥ mg/kg bodyweight			
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:			
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)				
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:			
Aspiration hazard :	Not classified			
(Aerosol) 20/20				
Vaporizer	Aerosol			

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to ac	quatic organisms nor to cause long-term adverse
-------------------	---	---

effects in the environment.

Hazardous to the aquatic environment, short–term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

(choile)			
2-butoxyethanol (111-76-2)			
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)		
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna		
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'		
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)			
LC50 - Fish [1]	0 - Fish [1] 0.362 mg/l		
EC50 - Crustacea [1]	0.018 mg/l		
ErC50 algae	7.6 mg/l Source: ECOTOX		

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.2. Persistence and degradability

(Aerosol) 20/20		
Persistence and degradability	Not rapidly degradable	
Propan-2-ol (67-63-0)		
Persistence and degradability	Not rapidly degradable	
2-butoxyethanol (111-76-2)		
Persistence and degradability Not rapidly degradable		
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)		
Persistence and degradability Not rapidly degradable		

12.3. Bioaccumulative potential

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.4. Mobility in soil

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)		
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID	

12.5. Other adverse effects

Ozone		: Not classified				
0.1			1.00			91 1 1

Other adverse effects : No additional information available

(Aerosol) 20/20		
Fluorinated greenhouse gases	False	
Propan-2-ol (67-63-0)		
Fluorinated greenhouse gases False		
2-butoxyethanol (111-76-2)		
Fluorinated greenhouse gases False		
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)		
Fluorinated greenhouse gases False		

SECTION 13: Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

26/04/2024 (Issue date) AU - en 7/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

ADG	IMDG	IATA				
14.1. UN number						
1950	1950	1950				
14.2. UN Proper Shipping Name						
AEROSOLS	AEROSOLS	Aerosols, flammable				
Transport document description						
Not applicable	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1				
14.3. Transport hazard class(es)						
2.1	2.1	2.1				
2	2	2				
14.4. Packing group						
Not applicable	Not applicable	Not applicable				
14.5. Environmental hazards						
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No				

14.6. Special precautions for user

Specific storage requirement : No data available Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

Special provision (ADG) : 63, 190, 277, 327, 344, 381

Limited quantities (ADG) : 11
Excepted quantities (ADG) : E0

Packing instructions (ADG) : P207, LP200 Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg

26/04/2024 (Issue date) AU - en 8/10

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Classification	
Aerosol 1	H222;H229
Press. Gas (Comp.)	H280
Eye Irrit. 2A	H319

Full text of H-statements	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 4	Flammable liquids, Category 4
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapour
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H312	Harmful in contact with skin

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Full text of H-statements	
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Safety Data Sheet (SDS), Australia

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.