

SAFETY DATA SHEET

Tango

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Tango
Product no.: B0032

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Cleaning product
Restricted to professional users.
Uses advised against : For professional use only. This product is not recommended for any industrial, professional or consumer use other than the identified uses above

1.3. Details of the supplier of the safety data sheet

Company and address: **Autosmart Australia**
11 Darrambal Close
NSW 2283 Rathmines
Australia
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)
autosmart@autosmartaustralia.com.au

Contact person: Russell Butler
E-mail: SHREQ@autosmart.co.uk
SDS date: 18/9/2025
SDS Version: 1.0

1.4. Emergency telephone number

In an Emergency call 000

NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at 1800 074 234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003-NCEC"
Local number +61 (0)2 8 014 4558

General Information. Transport Information. Mild medical Information:-
Autosmart Australia, Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

National Emergency Telephone Number:
In less severe situations call the Poisons Information Centre / Poison Information Hotline: 13 11 26 (Available 24/7 from anywhere in Australia)

SECTION 2: HAZARDS IDENTIFICATION

This material is considered hazardous according to the Work Health and Safety Regulations.

2.1. Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid

Skin Irrit. 2; H315, Causes skin irritation.
 Eye Irrit. 2; H319, Causes serious eye irritation.
 Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Warning

Hazard statement(s):

Combustible liquid (H227)
 Causes skin irritation. (H315)
 Causes serious eye irritation. (H319)
 Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s):

General:

Not applicable.

Prevention:

Wash hands thoroughly after handling. (P264)
 Avoid release to the environment. (P273)
 Wear protective gloves/protective clothing/eye protection/face protection. (P280)

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
 If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage:

Not applicable.

Disposal:

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances:

Does not contain any substances required to report

Additional labelling:

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance:	Identifiers:	% w/w:	Classification:	Note:
Hydrocarbons, C9-C12,n-alkanes, isoalkanes, cyclics, aromatics 2-25%	CAS No.: EC No.: 919-446-0	5-10%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT SE 2, H371	
Polydimethylsiloxane	CAS No.: 63148-62-9 EC No.: 613-156-5	3-5%	Eye Irrit. 2B, H320	[19]
2,2'-(octadec-9-enylimino)bisethanol	CAS No.: 25307-17-9 EC No.: 246-807-3	1-3%	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318	
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	CAS No.: 61789-77-3 EC No.: 263-087-6	<1%	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318	[19]

(R)-p-mentha-1,8-diene;d-limonene	CAS No.: 5989-27-5 EC No.: 227-813-5	<0.25%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Skin Sens. 1B, H317	
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7	<0.25%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Terpineol	CAS No.: 8000-41-7 EC No.: 232-268-1	<0.1%	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
citral	CAS No.: 5392-40-5 EC No.: 226-394-6	<0.05%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – bring the label or this safety data sheet.
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

IF ON SKIN: Wash with plenty of water and soap.
Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion:

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns:

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medic

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Not applicable.

5.2. Special hazards arising from the substance or mixture

Combustible liquid

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure call the NSW Poisons Information Centre on 13 11 26 (Available 24/7) in order to obtain further advice.

Hazchem Code: ●3Z

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

- Recommended storage material:* Keep only in original packaging.
- Storage conditions:* Dry, cool and well ventilated
- Incompatible materials:* Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

- propan-2-ol;isopropyl alcohol;isopropanol
- Long term exposure limit (8 hours) (ppm): 400
- Long term exposure limit (8 hours) (mg/m³): 983
- Short term exposure limit (15 minutes) (ppm): 500
- Short term exposure limit (15 minutes) (mg/m³): 1230

Workplace exposure standards for airborne contaminants (Safe Work Australia). (January 2024)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

- General recommendations:* Smoking, drinking and consumption of food is not allowed in the work area.
- Exposure scenarios:* There are no exposure scenarios implemented for this product.
- Exposure limits:* Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.
- Appropriate technical measures:* The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.
- Hygiene measures:* Take off contaminated clothing and wash it before reuse.
- Measures to avoid environmental exposure:* Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally: Use only protective equipment that carries the RCM symbol.


Respiratory Equipment:

Type:	Class:	Colour:	Standards:	:
Respiratory protection is not needed in the event of adequate ventilation.				

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is appropriately marked to a relevant standard. Check that the respirator fits tightly and the filter is changed regularly.


Gas and combination filter cartridges suitable for intended use, Full face mask respirators with replaceable filter cartridges suitable for intended use, half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use, can all be used.

Skin protection:

Recommended:	Type/Category:	Standards:	:
Dedicated work clothing should be worn.	-	-	


Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hand protection:

Material:	Glove thickness (mm):	Breakthrough time (min.):	Standards:	:
Nitrile	0,2	> 30	EN374-2, EN16523-1, EN388	

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: > 0.2 mm The selected gloves should have a breakthrough time of at least 2 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.

Eye protection:

Type:	Standards:	:
Safety glasses with side shields.	EN ISO 16321-1	

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Form:</i>	Liquid
<i>Colour:</i>	Orange
<i>Odour:</i>	Pleasant
<i>Odour threshold (ppm):</i>	No data available.

<i>pH:</i>	8.1
<i>pH in solution:</i>	6.7 (1%)
<i>Density (g/cm³):</i>	0.965 (20 °C)
<i>Kinematic viscosity:</i>	No data available.
<i>Particle characteristics:</i>	Does not apply to liquids.

Phase changes

<i>Melting point/Freezing point (°C):</i>	0
<i>Softening point/range (°C):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	100
<i>Vapour pressure:</i>	No data available.
<i>Relative vapour density:</i>	No data available.
<i>Decomposition temperature (°C):</i>	No data available.

Data on fire and explosion hazards

<i>Flash point (°C):</i>	62 Negative results have been obtained in the sustained combustibility test L.2, Part III, section 32 of the UN RTDG, Manual of Tests and Criteria.
<i>Flammability (°C):</i>	No data available.
<i>Auto-ignition temperature (°C):</i>	No data available.
<i>Explosion limits (% v/v):</i>	No data available.

Solubility

<i>Solubility in water:</i>	Completely soluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

9.2. Other information

<i>VOC (g/L):</i>	74
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available.

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Frost

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Product/substance Polydimethylsiloxane
 Species: Rabbit
 Route of exposure: Dermal
 Test: LD50
 Result: > 2000 mg/kg

Product/substance Polydimethylsiloxane
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: > 17000 mg/kg

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Test method: OECD 401
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: >300-2000 mg/kg

Product/substance Quaternary ammonium compounds, dicoco alkyl dimethyl, chlorides
 Test method: OECD 401
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: >300 - 2,000 mg/kg

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Test method: OECD 401
 Species: Rat
 Route of exposure: Oral
 Test: LD50
 Result: 5,840 mg/kg

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Test method: OECD 402
 Species: Rabbit
 Route of exposure: Dermal
 Result: >12,800 mg/kg

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Test method: OECD 403
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50
 Result: >10000 mg/kg

Based on available data for the mixture, the classification criteria are not met.

Skin corrosion/irritation

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Test method: OECD 404
 Species: Rabbit
 Description: Causes Burns
 Result: Adverse effect observed (Corrosive)

Product/substance	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
Test method:	OECD 404
Species:	Rabbit
Result:	Adverse effect observed (Corrosive)

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rabbit
Result:	No adverse effect observed (Not irritating)

Causes skin irritation.

Serious eye damage/irritation

Product/substance	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
Test method:	OECD 405
Species:	Rabbit
Result:	Adverse effect observed (Causes serious eye damage)

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Test method:	OECD 405
Species:	Rabbit
Result:	Adverse effect observed (Irritating)

Causes serious eye irritation.

Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

Skin sensitisation

Product/substance	2,2'-(octadec-9-enylimino)bisethanol
Test method:	OECD 406
Species:	Guinea pig
Result:	No adverse effect observed (not sensitising)

Product/substance	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
Test method:	OECD 406
Species:	Guinea pig
Result:	No adverse effect observed (not sensitising)

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Test method:	OECD 406
Species:	Guinea pig
Result:	No adverse effect observed (not sensitising)

Based on available data for the mixture, the classification criteria are not met.

Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

(R)-p-mentha-1,8-diene;d-limonene has been classified by IARC as a group 3 carcinogen.

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

STOT-single exposure

Based on available data for the mixture, the classification criteria are not met.

STOT-repeated exposure

Based on available data for the mixture, the classification criteria are not met.

Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Product/substance Polydimethylsiloxane
 Species: Fish
 Duration: 96 hours
 Test: LC50
 Result: > 10000 mg/L

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Test method: OECD 203
 Species: Fish, Danio rerio
 Duration: 96 hours
 Test: LC50
 Result: >0.1-1 mg/L

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Test method: OECD 202
 Species: Daphnia, Daphnia magna
 Duration: 96 hours
 Test: EC50
 Result: >0.01-0.1 mg/L

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Test method: OECD 201
 Species: Algae, Pseudokirchneriella subcapitata
 Duration: 72 hours
 Test: EC50
 Result: >0.01-0.1 mg/L

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Test method: OECD 201
 Species: Algae, Pseudokirchneriella subcapitata
 Duration: 72 hours
 Test: EC10
 Result: >0.01-0.1 mg/L

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Test method: OECD 211
 Species: Daphnia, Daphnia magna
 Duration: 72 hours
 Test: EC10
 Result: >0.001-0.01 mg/L

Product/substance Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
 Test method: OECD 203
 Species: Fish, Danio rerio
 Compartment: Freshwater
 Duration: 96 hours
 Test: LC50

Result:	>0.1 - 1 mg/L
Product/substance	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Compartment:	Freshwater
Duration:	72 hours
Test:	NOEC
Result:	>0.01 - 0.1 mg/L
Product/substance	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Compartment:	Freshwater
Duration:	72 hours
Test:	EC50
Result:	>0.1 - 1 mg/L
Product/substance	Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
Test method:	OECD 211
Species:	Daphnia, Daphnia magna
Duration:	21 days
Test:	NOEC
Result:	>0.1 - 1 mg/L
Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Test method:	OECD 203
Species:	Fish, Pimephales promelas
Duration:	96 hours
Test:	LC50
Result:	9640 mg/L
Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Test method:	OECD 202
Species:	Daphnia
Duration:	24 hours
Test:	LC50
Result:	>10000 mg/L
Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Algae
Duration:	7 days
Test:	NOEC
Result:	1800 mg/L
Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Bacteria
Test:	EC50
Result:	>1000 mg/L
Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Daphnia, Daphnia magna
Duration:	21 days
Test:	NOEC
Result:	30 mg/L

Based on available data for the mixture, the classification criteria are not met.

12.2. Persistence and degradability

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Conclusion: Readily biodegradable
 Test: OECD 301 D

Product/substance Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
 Conclusion: Inherently biodegradable
 Test: OECD 301 D

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Duration: 21 days
 Result: 95 %
 Conclusion: Readily biodegradable
 Test: OECD 301 E

12.3. Bioaccumulative potential

Product/substance 2,2'-(octadec-9-enylimino)bisethanol
 Conclusion: Bioaccumulation is not expected

Product/substance Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides
 LogKow: log Pow: 2.59 (@25 C)
 Conclusion: Bioaccumulation is not expected

Product/substance propan-2-ol;isopropyl alcohol;isopropanol
 Conclusion: Potential for bioaccumulation is low

12.4. Mobility in soil

propan-2-ol;isopropyl alcohol;isopropanol
 LogKoc = 1.1, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods




Dispose of contents/container to an approved waste disposal plant.

Specific labelling

Contaminated packing

SECTION 14: TRANSPORT INFORMATION

:	14.1 UN / ID:	14.2 UN proper shipping name:	14.3 Hazard class(es):	14.4 PG*:	14.5 Env**:	Other informatio n::
ADG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Naphtha (petroleum), hydrodesulfurized heavy)	Transport hazard class: 9 Label: 9 Classification code: M6	III	Yes	Limited quantities: 5 L Tunnel restriction code: (-)

	14.1 UN / ID:	14.2 UN proper shipping name:	14.3 Hazard class(es):	14.4 PG*:	14.5 Env**:	Other informatio n::
						See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Naphtha (petroleum), hydrodesulfurized heavy)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	Limited quantities: 5 L EmS: F-A S-F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Naphtha (petroleum), hydrodesulfurized heavy)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

-

Negative results have been obtained in the sustained combustibility test L.2, Part III, section 32 of the UN RTDG, Manual of Tests and Criteria.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: ●3Z

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

Restricted to professional users.

<i>Demands for specific education:</i>	No specific requirements.
<i>Control of major hazard facilities:</i>	Not applicable.
<i>Additional information:</i>	Not applicable.
<i>The Australian Inventory of Industrial Chemicals (AIIC):</i>	Polydimethylsiloxane is listed 2,2'-(octadec-9-enylimino)bisethanol is listed Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides is listed (R)-p-mentha-1,8-diene;d-limonene is listed propan-2-ol;isopropyl alcohol;isopropanol is listed Terpineol is listed citral is listed
<i>SUSMP:</i>	No Poison Schedule Allocated
<i>Sources:</i>	Model Work Health and Safety Regulations as at 1 January 2021.

15.2. Chemical safety assessment
No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.
H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H314, Causes severe skin burns and eye damage.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H320, Causes eye irritation
H336, May cause drowsiness or dizziness.
H371, May cause damage to organs.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ADG = The Australian Code for the Transport of Dangerous Goods by Road & Rail
AICIS = Australian Industrial Chemicals Introduction Scheme
AIIC = Australian Inventory of Industrial Chemicals
AS = Australian Standard
AS/NZS = Australian New Zealand Standard
ATE = Acute Toxicity Estimate
AUH = Hazard statements specific for Australia
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
EINECS = European Inventory of Existing Commercial chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
Hazchem = Hazardous chemicals
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NICNAS = National Industrial Chemicals Notification and Assessment Scheme (replaced by AICIS since 2020)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
RCM = Regulatory Mark of Conformity
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL = A specific concentration limit
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
SUSMP = Standard for the Uniform Scheduling of Medicines and Poisons
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
WHS = Work Health and Safety Regulations

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by the Work Health and Safety Regulations.
Refer to AS 1940-2017: The storage and handling of flammable and combustible liquids.

The safety data sheet is validated by

Russell Butler

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: AU-en