

SECTION 1: Product identifier**1.1. GHS Product identifier**

Product form : Mixture
Trade name : (Aerosol) Gloss White
Product code : 003498000076-AUS

1.2. Other means of identification

Other means of identification : AGWH003D
Synonyms : AGWH003D

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Spraying paint (spray can)
Restrictions on use : For professional use only

1.4. Details of manufacturer or importer

Autosmart Australia
11 Darrambal Close
Rathmines NSW 2283 NSW
Australia
T 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)
autosmart@autosmartaustralia.com.au - www.autosmartaustralia.com.au

1.5. Emergency phone number


Emergency number : NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident),
Call NCEC at 18000 74234 (toll free 24Hrs) - when calling please quote "AUTOSMART 29003-NCEC"
Local number +61 2 8 014 4558
General Information. Transport Information. Mild medical Information:-
Tel: 02 49 75 14 88 (Mon to Fri, 08:00 - 16:00 AEST)

SECTION 2: Hazard identification**2.1. Classification of the hazardous chemical****Classification according to the model Work Health and Safety Regulations (WHS Regulations)**

Aerosol, Category 1	H222;H229
Gases under pressure : Compressed gas	H280
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Gas cylinder

Exclamation mark

Signal word (GHS AU) : Danger
Contains : Xylene (mixture of isomers) (5 – 10 %);2-butoxyethanol (5 – 10 %);Acetone (25 – 50 %)
Hazard statements (GHS AU) : H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Precautionary statements (GHS AU)	: H280 - Contains gas under pressure; may explode if heated H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness P103 - Read carefully and follow all instructions. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, eye protection. P264 - Wash hands thoroughly after handling. P302+P352 - IF ON SKIN: Wash with plenty of water. P332+P313 - If skin irritation occurs: Get medical advice, medical attention. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER, a doctor if you feel unwell. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice, medical attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.
Additional hazard statements (GHS AU)	: AUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Acetone	67-64-1	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	68476-85-7	25 – 50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280 Flam. Liq. 1, H224
2-butoxyethanol	111-76-2	5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation), H331 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Titanium dioxide	13463-67-7	3.5 – 5	Not classified
Ethylbenzene	100-41-4	1 – 2.5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)	-	0 – 40.5	-

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethylbenzene (100-41-4)	
Australia - Occupational Exposure Limits	
Local name	Ethyl benzene
OES TWA	434 mg/m ³
	100 ppm
OES STEL	543 mg/m ³
	125 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
2-butoxyethanol (111-76-2)	
Australia - Occupational Exposure Limits	
Local name	2-Butoxyethanol (Butyl cellosolve; Butyl glycol; Ethylene glycol monobutyl ether; Glycol monobutyl ether)
OES TWA	96.9 mg/m ³
	20 ppm
OES STEL	242 mg/m ³
	50 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Acetone (67-64-1)	
Australia - Occupational Exposure Limits	
Local name	Acetone
OES TWA	1185 mg/m ³
	500 ppm
OES STEL	2375 mg/m ³
	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

Titanium dioxide (13463-67-7)	
Australia - Occupational Exposure Limits	
Local name	Titanium dioxide
OES TWA	10 mg/m ³
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Australia - Occupational Exposure Limits	
Local name	LPG (liquefied petroleum gas)
OES TWA	1800 mg/m ³
	1000 ppm
Remark (AU)	Carcinogenicity Category 1B - Presumed to have a carcinogenic potential for humans. The classification of a substance into this category is based largely on animal evidence where there is sufficient evidence to demonstrate carcinogenicity in animals or where there is limited evidence of carcinogenicity in humans and animals.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

8.2. Monitoring methods

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Wear recommended personal protective equipment.
Materials for protective clothing : The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Industrial Clothing: AS2919.
Hand protection : Protective gloves. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Protective Gloves: AS 2161.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard

Eye protection : Safety glasses. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Industrial Eye Protection: AS1336 and AS/NZS 1337.

Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

Skin and body protection : Wear suitable protective clothing

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Type	Standard
protective clothing	EN ISO 6530

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715.

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: white
Odour	: organic solvent
Odour threshold	: No data available
pH	: Not relevant - substance/mixture is non-soluble (in water).
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not applicable
Boiling point	: No data available
Flash point	: < -40 °C
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: < 20.5 mm ² /s
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 615 g/l
Fat solubility	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Acetone (67-64-1)	
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
Skin corrosion/irritation	: Causes skin irritation. pH: Not relevant - substance/mixture is non-soluble (in water).
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not relevant - substance/mixture is non-soluble (in water).
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
2-butoxyethanol (111-76-2)	
STOT-single exposure	May cause respiratory irritation.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
2-butoxyethanol (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
Aspiration hazard	: Not classified
(Aerosol) Gloss White	
Vaporizer	Aerosol
Not able to form a pool	Yes
Viscosity, kinematic	< 20.5 mm ² /s
Ethylbenzene (100-41-4)	
Viscosity, kinematic	0.6 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)' Remarks on result: 'other:'

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

2-butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

2-butoxyethanol (111-76-2)	
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

Acetone (67-64-1)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LC50 - Fish [1]	0.362 mg/l
EC50 - Crustacea [1]	0.018 mg/l
ErC50 algae	7.6 mg/l Source: ECOTOX
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.2. Persistence and degradability

(Aerosol) Gloss White	
Persistence and degradability	Not rapidly degradable

Ethylbenzene (100-41-4)	
Persistence and degradability	Not rapidly degradable

2-butoxyethanol (111-76-2)	
Persistence and degradability	Not rapidly degradable

Acetone (67-64-1)	
Persistence and degradability	Not rapidly degradable

Titanium dioxide (13463-67-7)	
Persistence and degradability	Not rapidly degradable

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.4. Mobility in soil

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

(Aerosol) Gloss White	
Fluorinated greenhouse gases	False

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations




Ethylbenzene (100-41-4)	
Fluorinated greenhouse gases	False
2-butoxyethanol (111-76-2)	
Fluorinated greenhouse gases	False
Acetone (67-64-1)	
Fluorinated greenhouse gases	False
Titanium dioxide (13463-67-7)	
Fluorinated greenhouse gases	False
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. UN Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description		
Not applicable	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement	: No data available
Shock sensitivity	: No data available

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950
Special provision (ADG) : 63, 190, 277, 327, 344, 381
Limited quantities (ADG) : 1I
Excepted quantities (ADG) : E0
Packing instructions (ADG) : P207, LP200
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Contains substance(s) listed on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

No additional information available

Australian Pesticides and Veterinary Medicines Authority (APVMA)

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 4/02/2025

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Classification	
Aerosol 1	H222;H229
Press. Gas (Comp.)	H280
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
STOT SE 3	H335

Full text of H-statements	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 4	Flammable liquids, Category 4
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapour
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

(Aerosol) Gloss White

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Full text of H-statements	
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), Australia

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.